




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F16D 65/16, 66/00	A1	(11) International Publication Number: WO 99/37939 (43) International Publication Date: 29 July 1999 (29.07.99)
(21) International Application Number: PCT/NL98/00566 (22) International Filing Date: 30 September 1998 (30.09.98) (30) Priority Data: PCT/NL98/00056 27 January 1998 (27.01.98) NL (71) Applicant (for all designated States except US): SKF INDUSTRIAL TRADING & DEVELOPMENT COMPANY B.V. [NL/NL]; P.O. Box 2350, NL-3430 DT Nieuwegein (NL). (72) Inventors; and (75) Inventors/Applicants (for US only): RINSMA, Andries, Christian [NL/NL]; Leidseweg 73, NL-3531 BE Utrecht (NL). ZWARTS, Jacobus [NL/NL]; Carmenlaan 5, NL-3438 VA Nieuwegein (NL). (74) Agent: DE BRUIJN, Leendert, C.; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: ACTUATOR COMPRISING FLEXIBLE ELEMENT, AND BRAKE CALLIPER COMPRISING SUCH ACTUATOR



(57) Abstract

An actuator (7) comprises a housing (4), a motor (8), an actuating member (25, 35) and a screw mechanism (10) providing a linear movement of the actuating member (25, 35) with respect to the housing (4) in response to a rotational movement of the motor (8), said screw mechanism (10) comprising a screw (24) and a nut (22) one of which is rotatably supported with respect to the housing (4). The screw mechanism (10) and the actuating member (25, 35) engage each other through a resilient intermediate pressure means (28, 29, 36).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Actuator comprising flexible element, and brake calliper comprising such actuator

The invention is related to an actuator comprising a housing, a motor, an actuating member and a screw mechanism providing a linear movement of the
5 actuating member with respect to the housing in response to a rotational movement of the motor, said screw mechanism comprising a screw and a nut one of which is rotatably supported with respect to the housing.

Such actuator is known from WO-A-9603301. The actuator comprises a screw mechanism, consisting of a screw and a nut which engage each other by means of
10 rollers having circumferential grooves. Such actuator provides a well defined axial displacement, and also a certain degree of reduction. Thus, a fairly small axial displacement is obtained in response to a considerable rotation of the screw. Consequently, the screw may exert a considerable axial force on the actuating member.

15 The proper operation of the screw mechanism can be assured as long as the screw, nut and rollers are subject to a well-defined, axial load. In such case, all components are loaded in accordance with their design requirements; moreover, the load may then reach a considerable level without causing damage to the screw mechanism.

20 A very unfavourable case however occurs when the screw mechanism is subjected to loadings having a transverse or radial component. The screw, nut and rollers are not designed to accommodate the transverse load components, and will be damaged.

The same occurs in case the actuator is loaded by a bending couple, which is
25 always associated with such transverse forces.

The object of the invention is to provide an actuator as described before, in which the problems related to transverse or radial loadings are circumvented or at least alleviated. This object is achieved in that the screw mechanism and the actuating member engage each other through a resilient intermediate pressure means. The
30 resilient intermediate pressure means is able to transfer the required actuating force from the screw mechanism onto the actuating member. Thus, its stiffness in axial direction should be rather high. In particular, the stiffness should be maintained at a

level where the required force/displacement relationship still provides the possibility to obtain the desired actuating force.

On the other hand, said resilient intermediate pressure means is not as stiff as a direct connection between the screw mechanism and the actuating member. This adapted stiffness has the advantage that extreme loadings, which have a certain transverse component or bending moment, are not directly and fully transmitted towards the screw mechanism. The resilient aspect of the force transmission between screw mechanism and actuating member makes these transverse or bending loadings less severe or even absent.

10 According to a first possible embodiment of the invention, the screw mechanism and the actuating member engage each other through spring elements. The spring elements may provide an asymmetric stiffness distribution with respect to the axis of the screw mechanism. The asymmetric character of the spring elements may be obtained in several ways, e.g. by more or stiffer springs at one side of the axis of the actuating member and the screw mechanism than at the opposite side.

The advantage of an asymmetric layout of the spring elements is that it may anticipate an asymmetric loading pattern under full loading. An example of a non-aligned loading, which increases with the load level, is to be attributed to flexing of the claw piece in the application of an actuator in a disc brake.

20 According to a second possibility, the screw mechanism and the actuating member engage each other by means of a resilient pressure pad.

Such pressure pad may have a relatively small thickness compared to its lateral dimensions. It can therefore easily be accommodated between the actuating member and the screw mechanism, within narrow space constraints.

25 The pressure pad preferably comprises two generally parallel wall members, said wall members being mutually connected along their circumference and enclosing a closed internal space.

The actuating member may be carried out as a piston, said piston being accommodated in a cylinder which forms a bore in the housing of the screw mechanism. Thus, the intermediate resilient pressure member is supported against the inside of the piston head.

According to a further development, the resilient intermediate pressure means engages a load measuring device. In particular, the load measuring device senses the pressure of the fluid.

5 The pressure developed in the fluid provides a reliable measure of the force exerted by the actuator. Possible non-axial or excentric loadings will not hamper the measurement of the overall axial loads to which the actuator is exposed. Thus, a reliable measurement is obtained.

If convenient, the internal space of the pressure pad is connected to a measuring channel, the free end of said channel being provided with the load
10 measuring device. Thereby, the actual measurement, e.g. by a piezoelectric sensor, may be carried out at particular location which is for instance shielded from the area where the actuating member is located (heat, moisture).

The invention is also related to a brake calliper comprising a housing, a motor, an actuating member and a screw mechanism providing a linear movement of the
15 actuating member with respect to the housing in response to a rotational movement of the motor, said screw mechanism comprising a screw and a nut one of which is rotatably supported with respect to the housing. The screw mechanism and the actuating member engage each other through a resilient intermediate pressure means for pressing the brake pads onto the brake disc.

20 The resilient intermediate pressure means of the brake calliper may engage a load measuring device as well. The internal space of the pressure pad is connected to a measuring channel, the free end of said channel being provided with the load measuring device.

The actual load measuring device (e.g. a piezoelectric sensor) may now be
25 situated at a location where the influence of the heat developed by the friction between the brake pads and the brake disc, is reduced.

The measuring channel may extend through the screw of the screw mechanism, the load measuring device being situated at the end of the screw which is opposite the pressure means. Furthermore, the load measuring device comprises a
30 load cell or load sensor, the electric signal line thereof extending through the internal space of the motor towards a connector or the like on the housing.

Preferably the fluid is a temperature resistant thermal oil.

The invention will be explained further with reference to the embodiments shown in the figures.

Figure 1 shows a first embodiment of a brake calliper comprising an actuator according to the invention.

5 Figure 2 shows a second embodiment.

Figure 3 shows a third embodiment.

The brake calliper shown in figure 1 comprises a claw piece 1, having a flange 2 supporting brake pad 3, and a housing 4 carrying brake pad 5. Between the brake pads 3 and 5, a brake disc 6 is accommodated.

10 Brake pad 5 is moveable towards, and away from, the other brake pad 3 by means of an actuator 7 which comprises an electric motor 8, a reduction gear mechanism 9, and a screw mechanism 10. The motor 8 has a stator 11 and a rotor 12, which rotor 12 is connected to a tubular connecting member 13 carrying a sun gear wheel 14.

15 The sun gear wheel 14 engages satellite gear wheels 15, which are accommodated on carrier 16. The satellite gear wheels 15 also engage the fixed ring gear wheel 17.

The carrier 16, in particular shaft 18 thereof, engages the screw mechanism 10 by means of tubular intermediate member 19.

20 The tubular intermediate member 19 is supported rotatably within the tubular connecting member 13 by means of bearings 20, 21.

The tubular intermediate member 19 is connected to nut 22 of the screw mechanism 10 which by means of rollers 23 engages screw 24. Screw 24 is held non-rotatably, but can move in axial direction. The nut 22 forms a unity with the
25 inner ring of the four point contact ball bearing 30, the outer ring 31 of which is supported in the housing 4.

The screw 24 engages the actuating member 25, in such a way that by means of the screw mechanism 10 the brake pad 5 can be moved towards, and away from, the other brake pad 3.

30 During a braking action, the brake pads 3, 5 may exhibit some play transverse with respect to the axis of screw mechanism 10. Thereby, the screw mechanism 10, in particular screw 24 thereof, may be loaded in a non-axial or non-aligned way.

In order to counteract the effects of such non-axial loadings, the surfaces 26 and 27 of the actuating members respectively the screw 24 engage each other by means of relatively stiff springs 28 and relatively flexible springs 29, whereby a locally different stiffness is obtained.

5 The stiffness ratio of these springs is selected in such a way that they simulate a flexing which is opposite to the flexing of the brake calliper, which flexing occurs as a result of the clamping forces by means of which the brake pads engage the brake disc. Thus the calliper flexing is reversed or counteracted in order to obtain an axial load on the screw mechanism.

10 The embodiment according to figure 2 corresponds to some extent to the embodiment of figure 1. The connecting member 13, which carries sun gear wheel 14, is now supported with respect to the housing by means of bearings 33, 34.

 Furthermore, the carrier 16, which carries satellite gear wheels 15 which engage both the sun gear wheel 14 and the ring gear wheel 17, is connected to the
15 nut 22 of the screw mechanism 10. This nut 22 at the same time constitutes the inner ring of the four point-ball bearing 30, the outer ring 31 of which is supported in the housing 4.

 Nut 22 engages screw 24 by means of rollers 23. The screw is held against rotation, but is able to move in axial direction. Thus, upon rotation of the nut 22, the
20 screw 24 moves backward and forward, thus moving the brake pads 3, 5 onto each other and onto the brake discs 6, or moving them away from each other.

 The actuating member is carried out as a piston 35, which is slidably held within the cylinder space 37 in the housing 4. By means of a groove nut connection 38, 38', the piston 35 is held non-rotatably, but slidably.

25 By means of further groove/nut connections 39, 39', screw 24 is also held non-rotatably, but slidably, with respect to piston 35.

 The screw engages piston head 40 by means of the interposed pressure pad 36. This pressure pad 36 has two parallel walls 41, connected at the circumference 42, e.g. by means of welding. The internal space enclosed between the parallel walls 41
30 is filled with a pressure medium 43, e.g. a hydraulic fluid.

 In case, as a result of the braking action, the brake pad 5 would tilt somewhat, and thereby causes somewhat misalignment between the axis of the piston 35 and the screw 24, pressure pad 36 may accommodate this misalignment. In this way, the

screw 24 is still mainly loaded in axial direction, thus allowing a proper function of the screw mechanism 10.

In the third embodiment, shown in figure 3, a load measuring device 50 has been applied. This may for instance be a piezoelectric sensor. The load measuring
5 device 50 is connected to a measuring channel 51, which is connected to the internal space 52 of the pressure pad 53.

Through a signal cable 54, the load measuring device 50 is connected to a control unit for further processing of the data thus obtained. As shown in the figure, the signal cable 54 is guided through the internal hollow space of the electric motor
10 7.

The internal space 52 and the measuring channel 51 may be filled with a thermal oil which is resistant to the high temperatures which may develop as a result of the friction between the brake pad 5 and the brake disc 6. Furthermore, a ceramic pad 55 may be arranged between the pressure pad 53 and the head of the piston 35,
15 so as to thermally insulate the thermal oil as a further precaution.

Claims

1. Actuator (7), comprising a housing (4), a motor (8), an actuating member (25) and a screw mechanism (10) providing a linear movement of the actuating member (25, 35) with respect to the housing (4) in response to a rotational movement of the motor (8), said screw mechanism (10) comprising a screw (24) and a nut (22) one of which is rotatably supported with respect to the housing (4), characterized in that the screw mechanism (10) and the actuating member (25, 35) engage each other through a resilient intermediate pressure means (28, 29; 36).

10

2. Actuator according to claim 1, wherein the screw mechanism (10) and the actuating member (25) engage each other through spring elements (28, 29).

3. Actuator according to claim 2, wherein the spring elements (28, 29) provide an asymmetric stiffness distribution with respect to the axis (32) of the screw mechanism (10).

4. Actuator according to any of the preceding claims, wherein the screw mechanism (10) and the actuating member (35) engage each other by means of a resilient pressure pad (36).

20

5. Actuator according to claim 4, wherein the pressure pad (36) comprises two generally parallel wall members (41), said wall members (41) being mutually connected along their circumference (42) and enclosing a closed internal space.

25

6. Actuator according to claim 5, wherein the closed internal space of the pressure pad is filled with a fluid (43).

7. Actuator according to any of the preceding claims, wherein the actuating member is carried out as a piston (35), said piston (35) being accommodated in a cylinder (37) which forms a part of the housing (4) of the screw mechanism (10).

30

8. Actuator according to claim 7, wherein the intermediate resilient pressure member (36) is supported against the inside of the piston head (40).

9. Actuator according to any of the preceding claims, wherein the resilient
5 intermediate pressure means (28, 29; 36) engages a load measuring device (50).

10. Actuator according to claims 6 and 9, wherein the load measuring device (50) senses the pressure of the fluid.

10 11. Actuator according to claim 10, wherein the internal space (52) of the pressure pad (36) is connected to a measuring channel (51), the free end of said channel (51) being provided with the load measuring device (50).

12. Actuator according to claim 9, 10, wherein the load measuring device (50)
15 comprises a piezoelectric sensor.

13. Brake calliper for a disc brake, comprising an actuator (7) according to any of the preceding claims, said actuator comprising a housing (4), a motor (8), an actuating member (25, 35) and a screw mechanism (10) providing a linear movement
20 of the actuating member with respect to the housing (4) in response to a rotational movement of the motor (8), said screw mechanism (10) comprising a screw (24) and a nut (22) one of which is rotatably supported with respect to the housing (4), a claw piece (1) carrying two opposite brake pads (3,5) between which a brake disc (6) can be accommodated, the housing (4) of the actuator (7) being connected to the claw
25 piece (1) and the actuating member (25, 35) being connected to one of the brake pads (3,5), characterized in that the screw mechanism (10) and the actuating member (25, 35) engage each other through a resilient intermediate pressure means (28, 29; 36).

14. Brake calliper according to claim 13, wherein the resilient intermediate
30 pressure means (28, 29; 36) engages a load measuring device (50).

15. Brake calliper according to claim 14, wherein the load measuring device (50) senses the pressure of the fluid.

16. Brake calliper according to claim 15, wherein the internal space (52) of the pressure pad (36) is connected to a measuring channel (51), the free end of said channel (52) being provided with the load measuring device (50).

5 17. Brake calliper according to claim 16, wherein the measuring channel (52) extends through the screw (24) of the screw mechanism, the load measuring device (50) being situated at the end of the screw (24) which is opposite the pressure means (28, 29; 36).

10 18. Brake calliper according to claim 17, wherein the load measuring device (50) comprises a load cell or load sensor, the electric signal (54) line thereof extending through the internal space of the motor (8) towards a connector or the like on the housing.

15 19. Brake calliper according to claim 16, 17 or 18, wherein the fluid is a high-temperature resistant thermal oil.

1/3






fig-2





fig-3



INTERNATIONAL SEARCH REPORT

International Application No
PCT/NL 98/00566

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 F16D65/16 F16D66/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 F16D H02K F16F B61H G01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	DE 196 07 759 C (KORTHAUS ET AL.) 28 May 1997 see column 3, line 28 - column 4, line 68; figures	1,2,7-9
X A	EP 0 285 773 A (ROBERT BOSCH) 12 October 1988 see column 3, line 31 - column 4, line 21; figures	1,2,9-12
X A	US 4 546 295 A (WICKHAM ET AL.) 8 October 1985 see column 8, line 44 - column 10, line 39; figure 3	1,2 9,13,14
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

22 December 1998

Date of mailing of the international search report

04/01/1999

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Becker, R

PCT/NL 98/00566

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Inter nal Application No

PCT/NL 98/00566

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 35 02 275 A (WABCO WESTINGHOUSE FAHRZEUGBREMSSEN) 24 July 1986 see the whole document -----	1,4,5,9, 10,12
A	GB 2 078 983 A (BRITISH AEROSPACE) 13 January 1982 see the whole document -----	4-6, 9-11, 14-16

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter: 1st Application No

PCT/NL 98/00566

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19607759 C	28-05-1997	NONE	
EP 285773 A	12-10-1988	DE 3712077 A DE 3870964 A JP 2567270 B JP 63262534 A	27-10-1988 17-06-1992 25-12-1996 28-10-1988
US 4546295 A	08-10-1985	AU 560623 B AU 2784184 A AU 558094 B AU 2784284 A AU 2784384 A AU 558095 B AU 2784484 A AU 559873 B AU 2784584 A AU 558502 B AU 2784684 A CA 1217149 A CA 1218315 A CA 1228305 A CA 1224424 A CA 1230063 A DE 3467220 A DE 3467221 A DE 3470086 A DE 3472708 A DE 3473014 A EP 0126582 A EP 0125870 A EP 0125871 A EP 0125872 A EP 0125873 A EP 0125874 A GB 2141501 A,B GB 2141502 A,B GB 2141503 A,B GB 2141504 A GB 2141800 A,B GB 2140107 A,B IN 161424 A IN 161425 A IN 161426 A IN 161427 A IN 160902 A JP 60008148 A JP 59212541 A JP 59231228 A JP 60008149 A JP 59231803 A JP 59231229 A US 4546296 A US 4546298 A US 4546297 A US 4532462 A US RE32610 E	09-04-1987 15-11-1984 15-01-1987 15-11-1984 15-11-1984 15-01-1987 15-11-1984 19-03-1987 15-11-1984 29-01-1987 15-11-1984 27-01-1987 24-02-1987 20-10-1987 21-07-1987 08-12-1987 10-12-1987 10-12-1987 28-04-1988 18-08-1988 01-09-1988 28-11-1984 21-11-1984 21-11-1984 21-11-1984 21-11-1984 21-11-1984 19-12-1984 19-12-1984 19-12-1984 19-12-1984 03-01-1985 21-11-1984 28-11-1987 28-11-1987 28-11-1987 28-11-1987 15-08-1987 17-01-1985 01-12-1984 25-12-1984 17-01-1985 26-12-1984 25-12-1984 08-10-1985 08-10-1985 08-10-1985 30-07-1985 23-02-1988
DE 1431129 B	30-07-1970	NONE	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/NL 98/00566

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 632181	A	04-01-1995	DE 4322133 A	12-01-1995
DE 3935425	A	25-04-1991	WO 9106452 A	16-05-1991
			EP 0450028 A	09-10-1991
FR 2449015	A	12-09-1980	DD 149195 A	01-07-1981
			DE 3005772 A	28-08-1980
DE 19652230	A	18-06-1998	AU 5853998 A	15-07-1998
			WO 9827357 A	25-06-1998
WO 9730294	A	21-08-1997	AU 1961397 A	02-09-1997
			GB 2324843 A	04-11-1998
WO 9603301	A	08-02-1996	DE 19511287 A	25-01-1996
			CZ 9600594 A	17-07-1996
			EP 0728089 A	28-08-1996
			HU 75406 A	28-05-1997
			PL 313522 A	08-07-1996
			SK 29496 A	01-10-1996
			US 5829557 A	03-11-1998
WO 9717553	A	15-05-1997	EP 0854986 A	29-07-1998
EP 263752	A	13-04-1988	FR 2604763 A	08-04-1988
US 3866721	A	18-02-1975	NONE	
US 5014827	A	14-05-1991	CA 2001228 A	20-01-1991
EP 173658	A	05-03-1986	SE 446897 B	13-10-1986
			JP 61036525 A	21-02-1986
			SE 8403412 A	28-12-1985
DE 3502275	A	24-07-1986	NONE	
GB 2078983	A	13-01-1982	NONE	